

# Castrads®

## Declaration of Performance

No. 202009-1018

### Curved Florence 2 Column 685mm

<b>Unique product code:</b>	CUR-F2C-687
<b>Type, batch or serial number:</b>	CUR-F2C-687
<b>Intended use of the construction product:</b>	In heating systems in buildings
<b>Manufacturer:</b>	Castrads Ltd 1 Kenwood Road North Reddish SK5 6PH, Manchester, United Kingdom
<b>System of AVCP:</b>	System 3
<b>Harmonized standard:</b>	EN 442-1:2014
<b>Notified body:</b>	Politecnico di Milano
<b>Test report number:</b>	ENE/MRT.RES.01003_A

### Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	
Release of dangerous substances	None	
Pressure tightness	No leakage at 1.3 x maximum operating pressure [kPa]	
Surface temperature	Maximum 120°C	
Resistance to pressure	No breakage at 1.69 x maximum operating pressure [kPa] Maximum operating pressure: 1000 [kPa]	EN 442-1:2014
Rated thermal outputs	See appendix 1	
Thermal output in different operating conditions (characteristic curve)	$\phi = K_m \cdot \Delta T^n$ . See appendix for factor $K_m$ and exponent $n$	
Resistance against corrosion	No corrosion after 100h humidity	
Resistance against minor impact:	Class 0	

**Signed for and on behalf of the manufacturer by:**

Nicholas Baylis  
CEO  
Stockport, England  
24th June 2026





## Appendix to DOP No. 202009-1018: Dimensions and thermal outputs

Panel dimensions: 787mm high when floor standing, 67mm deep for all numbers of sections. See table for length.

SKU	Num of sec.	Length, mm	Output (Watts, DT50)	Output (Watts, DT30)	Factor, Km	Exponent, n
CUR-F2C-687-03	3	165	146	76	1.019	1.2693
CUR-F2C-687-04	4	210	195	102	1.359	1.2693
CUR-F2C-687-05	5	255	243	127	1.698	1.2693
CUR-F2C-687-06	6	300	292	153	2.038	1.2693
CUR-F2C-687-07	7	345	341	178	2.377	1.2693
CUR-F2C-687-08	8	390	390	204	2.717	1.2693
CUR-F2C-687-09	9	435	438	229	3.057	1.2693
CUR-F2C-687-10	10	480	487	255	3.396	1.2693
CUR-F2C-687-11	11	525	536	280	3.736	1.2693
CUR-F2C-687-12	12	570	584	306	4.076	1.2693
CUR-F2C-687-13	13	615	633	331	4.415	1.2693
CUR-F2C-687-14	14	660	682	356	4.755	1.2693
CUR-F2C-687-15	15	705	730	382	5.095	1.2693
CUR-F2C-687-16	16	750	779	407	5.434	1.2693
CUR-F2C-687-17	17	795	828	433	5.774	1.2693
CUR-F2C-687-18	18	840	876	458	6.114	1.2693
CUR-F2C-687-19	19	885	925	484	6.453	1.2693
CUR-F2C-687-20	20	930	974	509	6.793	1.2693
CUR-F2C-687-21	21	975	1023	535	7.132	1.2693
CUR-F2C-687-22	22	1020	1071	560	7.472	1.2693
CUR-F2C-687-23	23	1065	1120	586	7.812	1.2693
CUR-F2C-687-24	24	1110	1169	611	8.151	1.2693
CUR-F2C-687-25	25	1155	1217	637	8.491	1.2693
CUR-F2C-687-26	26	1200	1266	662	8.831	1.2693
CUR-F2C-687-27	27	1245	1315	687	9.170	1.2693
CUR-F2C-687-28	28	1290	1363	713	9.510	1.2693
CUR-F2C-687-29	29	1335	1412	738	9.850	1.2693
CUR-F2C-687-30	30	1380	1461	764	10.189	1.2693
CUR-F2C-687-31	31	1425	1509	789	10.529	1.2693
CUR-F2C-687-32	32	1470	1558	815	10.868	1.2693
CUR-F2C-687-33	33	1515	1607	840	11.208	1.2693
CUR-F2C-687-34	34	1560	1656	866	11.548	1.2693
CUR-F2C-687-35	35	1605	1704	891	11.887	1.2693
CUR-F2C-687-36	36	1650	1753	917	12.227	1.2693
CUR-F2C-687-37	37	1695	1802	942	12.567	1.2693
CUR-F2C-687-38	38	1740	1850	968	12.906	1.2693
CUR-F2C-687-39	39	1785	1899	993	13.246	1.2693
CUR-F2C-687-40	40	1830	1948	1018	13.586	1.2693