

# Castrads®

## Declaration of Performance

No. 202009-1044

Florence 4 Column 300mm

<b>Unique product code:</b>	SMC-F4C-302
<b>Type, batch or serial number:</b>	SMC-F4C-302
<b>Intended use of the construction product:</b>	In heating systems in buildings
<b>Manufacturer:</b>	Castrads Ltd 1 Kenwood Road North Reddish SK5 6PH, Manchester, United Kingdom
<b>System of AVCP:</b>	System 3
<b>Harmonized standard:</b>	EN 442-1:2014
<b>Notified body:</b>	Politecnico di Milano
<b>Test report number:</b>	ENE/MRT.ITPL.01005

### Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	
Release of dangerous substances	None	
Pressure tightness	No leakage at 1.3 x maximum operating pressure [kPa]	
Surface temperature	Maximum 120°C	
Resistance to pressure	No breakage at 1.69 x maximum operating pressure [kPa] Maximum operating pressure: 1000 [kPa]	EN 442-1:2014
Rated thermal outputs	See appendix 1	
Thermal output in different operating conditions (characteristic curve)	$\phi = K_m \cdot \Delta T^n$ . See appendix for factor $K_m$ and exponent $n$	
Resistance against corrosion	No corrosion after 100h humidity	
Resistance against minor impact:	Class 0	

**Signed for and on behalf of the manufacturer by:**

Nicholas Baylis  
CEO  
Stockport, England  
3rd May 2026





## Appendix to DOP No. 202009-1044: Dimensions and thermal outputs

Panel dimensions: 402mm high when floor standing, 141mm deep for all numbers of sections. See table for length.

SKU	Num of sec.	Length, mm	Output (Watts, DT50)	Output (Watts, DT30)	Factor, Km	Exponent, n
SMC-F4C-302-03	3	165	126	66	0.920	1.2581
SMC-F4C-302-04	4	210	168	89	1.226	1.2581
SMC-F4C-302-05	5	255	210	111	1.533	1.2581
SMC-F4C-302-06	6	300	252	133	1.840	1.2581
SMC-F4C-302-07	7	345	295	155	2.146	1.2581
SMC-F4C-302-08	8	390	337	177	2.453	1.2581
SMC-F4C-302-09	9	435	379	199	2.759	1.2581
SMC-F4C-302-10	10	480	421	221	3.066	1.2581
SMC-F4C-302-11	11	525	463	243	3.373	1.2581
SMC-F4C-302-12	12	570	505	266	3.679	1.2581
SMC-F4C-302-13	13	615	547	288	3.986	1.2581
SMC-F4C-302-14	14	660	589	310	4.292	1.2581
SMC-F4C-302-15	15	705	631	332	4.599	1.2581
SMC-F4C-302-16	16	750	673	354	4.906	1.2581
SMC-F4C-302-17	17	795	715	376	5.212	1.2581
SMC-F4C-302-18	18	840	757	398	5.519	1.2581
SMC-F4C-302-19	19	885	800	420	5.825	1.2581
SMC-F4C-302-20	20	930	842	443	6.132	1.2581
SMC-F4C-302-21	21	975	884	465	6.439	1.2581
SMC-F4C-302-22	22	1020	926	487	6.745	1.2581
SMC-F4C-302-23	23	1065	968	509	7.052	1.2581
SMC-F4C-302-24	24	1110	1010	531	7.358	1.2581
SMC-F4C-302-25	25	1155	1052	553	7.665	1.2581
SMC-F4C-302-26	26	1200	1094	575	7.972	1.2581
SMC-F4C-302-27	27	1245	1136	597	8.278	1.2581
SMC-F4C-302-28	28	1290	1178	620	8.585	1.2581
SMC-F4C-302-29	29	1335	1220	642	8.891	1.2581
SMC-F4C-302-30	30	1380	1262	664	9.198	1.2581
SMC-F4C-302-31	31	1425	1304	686	9.505	1.2581
SMC-F4C-302-32	32	1470	1347	708	9.811	1.2581
SMC-F4C-302-33	33	1515	1389	730	10.118	1.2581
SMC-F4C-302-34	34	1560	1431	752	10.424	1.2581
SMC-F4C-302-35	35	1605	1473	775	10.731	1.2581
SMC-F4C-302-36	36	1650	1515	797	11.038	1.2581
SMC-F4C-302-37	37	1695	1557	819	11.344	1.2581
SMC-F4C-302-38	38	1740	1599	841	11.651	1.2581
SMC-F4C-302-39	39	1785	1641	863	11.957	1.2581
SMC-F4C-302-40	40	1830	1683	885	12.264	1.2581